



- 8'-8" x 7'-0" FINISHED OPENINGS for ROLL-UP DOORS (by TRAC-RITE DOOR CO.)
- LOAD BEARING WALL 10'-0" o.c. TYPICAL
3 5/8" x 1 5/8" x 18ga. "Cee" STEEL STUDS @ 2'-0" o.c. (SEE DETAILS ON SHEET #___)
- 8'-8" x 6'-6" FINISHED OPENINGS for INTERIOR ROLL-UP DOORS (by TRAC-RITE DOOR CO.)
- 3'-0" x 7'-0" FINISHED OPENINGS for SWING DOORS (by TRAC-RITE DOOR, CO.)
- (1) HOUR FIRE ENCLOSURE @ STAIR/LIFT
(1) LAYER OF 5/8" FIRE STOP (TYPE X GYPSUM WALLBOARD) SHEETROCK ON EACH SIDE TYPICAL (3) WALLS (SEE DETAILS ON SHEET #___) per GYPSUM ASSOC. FILE 1206 or UNDERWRITERS LAB DESIGN U425
- DENOTES HANDICAPPED/WHEELCHAIR ACCESSIBLE UNITS
- 8'-8" x 7'-0" FINISHED OPENINGS for ROLL-UP DOORS (by TRAC-RITE DOOR CO.)
- 3'-8" x 7'-0" FINISHED OPENINGS for 3'-4" x 6'-10" SWING DOORS (by PLYCO)

LOWER LEVEL FLOOR PLAN for 50' x 200' TWO-STORY MINI-STORAGE BUILDING

1/8" = 1'-0"